EAST Search History

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
S106	2226	((authenticat$3 authorizat$3) NEAR3 (key)) NEAR5 ($2code)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/12 21:01
S107	313	S106 AND ((@ad <= "19990205") or (@rlad <= "1990205"))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/02/12 21:02
S108	0	S107 AND "380".ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/02/12 21:02
S109	97	S107 AND "380"/$.ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/02/12 21:02
S110	787	((authenticat$3 authorizat$3) NEAR3 (key)) NEAR5 (encod$3 decod$3)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/12 21:03
S111	115	S110 AND ((@ad <= "19990205") or (@rlad <= "1990205"))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/02/12 21:03
S112	1640	((((store storage memory cache hold) NEAR5 (key)) WITH (STB STT receiver terminal)) AND ((@ad <= "19990205") or (@rlad <= "1990205"))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/02/12 21:16
S113	253	S112 AND "380"/$.ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/02/12 21:17

S114	93	((((store storage memory cache hold) NEAR5 (key)) WITH (STB STT receiver terminal)) SAME ((compar$4 verify verification) NEAR5 key) AND ((@ad <= "19990205") or (@rlad <= "1990205"))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/02/12 21:18
S115	137	S112 AND "713"/$.ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/02/12 21:23
S116	26	S115 NOT S113	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/02/12 21:23
S117	49	S112 AND "725"/$.ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/02/12 21:28
S118	34	S117 NOT (S115 S113)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/02/12 21:29
S119	52	713/173.CCLS. AND ((@ad <= "19990205") or (@rlad <= "1990205"))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/02/12 21:32
S120	110	380/286.CCLS. AND ((@ad <= "19990205") or (@rlad <= "1990205"))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/02/12 21:37
S121	7875	((authenticat$3 authorizat$3) NEAR3 (key)) NEAR5 (encrypt$3 decrypt$3)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/12 21:40
S122	17	((((store storage memory cache hold) NEAR5 (key)) WITH (STB STT receiver terminal)) AND ((compar$4 verify verification) NEAR5 key) AND S121 AND ((@ad <= "19990205") or (@rlad <= "1990205"))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/02/12 21:41

S123	325	380/277.CCLS. AND (((@ad <= "19990205") or (@rlad <= "1990205"))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/02/12 21:44
S124	588	(server headend) WITH (dynamic$6 assign$4) WITH ((MAC "medium access control") ADJ2 (ID identification address number))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/02/13 05:42
S125	36	S124 AND (((@ad <= "19990205") or (@rlad <= "1990205"))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/02/13 05:43
S126	401	bookmark and "725"/$. ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/03/12 17:05
S127	22	bookmark with (commercial ad) and "725"/$.ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/03/12 17:06
S128	99	bookmark and "725"/$. ccls.	USPAT	OR	ON	2009/03/12 17:06
S129	1	"6353929".pn.	USPAT	OR	ON	2009/03/12 18:07
S130	0	(725/50 725/132,140,152). ccls. AND (((@ad <= "1990205") or (@rlad <= "1990205"))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/03/12 18:16
S131	206	(725/50.ccls. 725/132,140,152.ccls.) AND (((@ad <= "19990205") or (@rlad <= "19990205"))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/03/12 18:17
S132	2345	(key encrypt$3 RSA) WITH ((MAC LAN "local area network" "media access" "802.$3") NEAR2 (address ID identification number))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/03/12 19:00
S133	184	S132 AND (((@ad <= "19990205") or (@rlad <= "19990205"))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/03/12 19:00

S134	325	380/277.ccls. AND ((@ad <= "19990205") or (@rlad <= "1990205"))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/03/15 18:38
S135	17594	($2crypt$3 $2scrambl$3 key) WITH ((MAC terminal destination subscriber device network) NEAR3 (address ID identification))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/03/15 18:42
S136	21246	($2crypt$3 $2scrambl$3 key) WITH ((MAC terminal destination subscriber device network Internet IP web) NEAR3 (address ID identification))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/03/15 18:42
S137	57	S134 AND S136	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/03/15 18:42
S138	2	"5752080".pn.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/03/15 18:50
S139	43635	($2assign$4 $2allocat$3) WITH ((MAC terminal destination device network Internet IP web) NEAR3 (address ID identification))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/03/15 19:25
S140	35722	($2assign$4 $2allocat$3) NEAR5 ((MAC terminal destination device network Internet IP web) NEAR3 (address ID identification))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/03/15 19:26
S141	418	"380"/$.ccls. AND S140	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/03/15 19:26
S142	72	S141 AND ((@ad <= "19990205") or (@rlad <= "1990205"))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2009/03/15 19:26
S143	2472	($2scrambl$3 key encrypt $3 RSA) WITH ((Ethernet MAC LAN "local area network" "media access" "802.$3") NEAR2 (address ID identification number))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/03/15 20:35

| S144 | 133 | S143 AND ((@ad <= "19990205") or (@rlad <= "1990205")) | US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB | OR | OFF | 2009/03/15 20:35 |

3/30/09 3:13:35 AM
C:\ Documents and Settings\ RBrown1\ My Documents\ EAST\ Workspaces\ 09-496769b.wsp